

ASUS「PRIME B350-PLUS」スペック表

製品名	PRIME B350-PLUS
対応CPU	AMD AM4 Socket for AMD Ryzen™/7th Generation A-series/Athlon™ Processors Supports CPU up to 8 cores * Refer to <a href="http://www.asus.com">www.asus.com</a> for CPU support list
チップセット	AMD B350
対応メモリ	AMD Ryzen™ Processors 4 x DIMM, Max. 64GB, DDR4 3200(O.C.)/2933(O.C.)/2666/2400/2133 MHz Non-ECC, Un-buffered Memory *1 AMD 7th Generation A-series/Athlon™ Processors 4 x DIMM, Max. 64GB, DDR4 2400/2133 MHz Non-ECC, Un-buffered Memory Dual Channel Memory Architecture * Hyper DIMM support is subject to the physical characteristics of individual CPUs. * Refer to <a href="http://www.asus.com">www.asus.com</a> for the Memory QVL (Qualified Vendors Lists).
画面出力機能	Integrated AMD Radeon™ R Series Graphics in the 7th Generation A-Series APU Multi-VGA output support : HDMI/DVI/RGB ports - Supports HDMI 1.4b with max. resolution 4096 x 2160 @ 24 Hz / 2560 x 1600 @ 60 Hz - Supports DVI-D with max. resolution 1920 x 1200 @ 60 Hz - Supports RGB with max. resolution 1920 x 1200 @ 60 Hz Maximum shared memory of 2048 MB
拡張スロット	AMD Ryzen™ Processors 1 x PCIe 3.0/2.0 x16 (x16 mode) AMD 7th Generation A-series/Athlon™ Processors 1 x PCIe 3.0/2.0 x16 (x8 mode) AMD B350 chipset 1 x PCIe 2.0 x16 (max at x4 mode) *2 2 x PCIe 2.0 x1 2 x PCI
マルチGPU対応	Supports AMD CrossFireX™ Technology
ストレージ機能	AMD B350 chipset : 4 x SATA 6Gb/s port(s), gray, Support Raid 0, 1, 10 AMD Ryzen™/7th Generation A-series/Athlon™ Processors : 2 x SATA 6Gb/s port(s), gray, AMD Ryzen™ Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 4 mode)*3 AMD 7th Generation A-series/Athlon™ Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280/22110 storage devices support (SATA & PCIE 3.0 x 2 mode)*4
LAN機能	Realtek® RTL8111H, 1 x Gigabit LAN Controller(s)
オーディオ機能	Realtek® ALC887 8-Channel High Definition Audio CODEC
USB機能	AMD Ryzen™/7th Generation A-series/Athlon™ Processors : 4 x USB 3.0 port(s) (4 at back panel, blue) AMD B350 chipset : 2 x USB 3.1 port(s) (2 at back panel, teal blue) AMD B350 chipset : 2 x USB 3.0 port(s) (2 at mid-board) AMD B350 chipset : 6 x USB 2.0 port(s) (2 at back panel, black, 4 at mid-board)
搭載機能	ASUS 5X Protection III : - ASUS SafeSlot Core: Fortified PCIe Slot prevents damage - ASUS LANGuard: Protects against LAN surges, lightning strikes and static-electricity discharges! - ASUS Overvoltage Protection: World-class circuit-protecting power design - ASUS Stainless-Steel Back I/O: 3X corrosion-resistance for greater durability! - ASUS DIGI+ VRM: 6 Phase digital power design ASUS Exclusive Features : - AI Suite 3 - Ai Charger - Turbo LAN - PC Cleaner ASUS Quiet Thermal Solution : - Stylish Fanless Design Heat-sink solution & MOS Heatsink - ASUS Fan Xpert 2+ ASUS EZ DIY : - ASUS CrashFree BIOS 3 - ASUS EZ Flash 3 - ASUS UEFI BIOS EZ Mode - Multi-language BIOS ASUS Q-Design : - ASUS Q-Slot - ASUS Q-DIMM
基板上インターフェース	1 x Fan RGB header 1 x USB 3.0 connector(s) support(s) additional 2 USB 3.0 port(s) (19-pin) 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s) 1 x M.2 Socket 3 with M Key, type 2242/2260/2280/22110 storage devices support (SATA mode & PCIE mode) 1 x COM port(s) connector(s) 6 x SATA 6Gb/s connector(s) 1 x CPU Fan connector(s) (1 x 4 -pin) 2 x Chassis Fan connector(s) (2 x 4 -pin) 1 x S/PDIF out header(s) 1 x 24-pin EATX Power connector(s) 1 x 8-pin ATX 12V Power connector(s) 1 x Front panel audio connector(s) (AAFP) 1 x System panel(s) 1 x Clear CMOS jumper(s)

バックパネルインターフェース	1 x PS/2 keyboard/mouse combo port(s) 1 x DVI-D 1 x D-Sub 1 x HDMI 1 x LAN (RJ45) port(s) 2 x USB 3.1 (teal blue) 4 x USB 3.0 (blue) 2 x USB 2.0 3 x Audio jack(s)
主な付属品	User's manual I/O Shield 2 x SATA 6Gb/s cable(s) 1 x M.2 Screw Package 1 x Supporting DVD
BIOS	128 Mb Flash ROM, UEFI AMI BIOS, PnP,WfM2.0,SM BIOS 3.0, ACPI 6.1, Multi-language BIOS, ASUS EZ Flash 3, ASUS CrashFree BIOS 3, My Favorites, Last Modified log, F12 PrintScreen, ASUS DRAM SPD (Serial Presence Detect) memory information, F6 Qfan Control
管理機能	—
対応OS	Windows® 10 64-bit
フォームファクター	ATX(305mm×237mm)
備考	1*Due to AMD Ryzen™ Processor limitation, More than DDR4-2666 is supported by one DIMM per channel only. 2*PCIeX16_2 slot shares bandwidth with PCIeX1_1 and PCIeX1_2. 3*When a SATA / PCIE mode M.2 device is installed, the M.2 Socket shares bandwidth with the SATA6G_5/6 ports. 4*When a SATA mode M.2 device is installed, the M.2 Socket shares bandwidth with the SATA6G_5/6 ports

※製品の仕様は製品の改善のために予告なく変更することがあります。

※製品の仕様は2017年3月現在のものです。